Emeri (idigbo).

| Terminalia ivorensis |





All images used are for representation purposes only.

Emeri (idigbo).

A form of idigbo and a durable stable hardwood from Ghana. It should not be confused with Framire from other parts of West Africa, which is prone to brittle-heart, thunder-shake and tension wood. Emeri requires care in machining due to the interlocked grain structure, and all forms of Idigbo are prone to leach a yellow dye when wet, so require a leach-resistant primer when being painted. Overall, a good low-cost general-purpose timber which has been used as an Oak substitute although softer and lighter than Oak. Its natural colour is yellow.

For more information please visit: **www.sykestimber.co.uk**

Origin. Emire Idigbo is from Ghana and is notably superior than Framire Idigbo from other nations in West Africa.	**Density.** 560kgs/m^3
Availability. Square edged kiln dried boards.	**Movement in Service.** Small.
Grade. 'Sykes Grade' Emeri upgraded from FAS.	**Thicknesses available.** 26mm, 32mm, 38mm, 52mm, 63mm, 76mm, 100mm (AD)
Colour. Yellow.	**Length and width specification.** 1.8m and longer x 100mm and wider.
Applications. General joinery and interior furniture.	**Basic price Level.** Low.
Durability. Durable.	**Summary.** Cost effective and stable timber for general purposes, use a leach resistant primer if painting.

Sykes Timber.
Carlyon Road | Atherstone | Warwickshire | CV9 1JD

Phone.
01827 718951

Email.
sales@sykestimber.co.uk

Web.
www.sykestimber.co.uk